

AP-500/850 Gal. Pump Tank Calibration Chart

Height (in.)	Volume (Gal)						
70.5	918.35	59.5	775.06	48.25	628.52	37	481.97
70.25	915.10	59.25	771.81	48	625.26	36.75	478.72
70	911.84	59	768.55	47.75	622.01	36.5	475.46
69.75	908.58	58.75	765.29	47.5	618.75	36.25	472.20
69.5	905.33	58.5	762.04	47.25	615.49	36	468.95
69.25	902.07	58.25	758.78	47	612.24	35.75	465.69
69	898.81	58	755.52	46.75	608.98	35.5	462.43
68.75	895.56	57.75	752.27	46.5	605.72	35.25	459.18
68.5	892.30	57.5	749.01	46.25	602.47	35	455.92
68.25	889.04	57.25	745.76	46	599.21	34.75	452.66
68	885.79	57	742.50	45.75	595.95	34.5	449.41
67.75	882.53	56.75	739.24	45.5	592.70	34.25	446.15
67.5	879.27	56.5	735.99	45.25	589.44	34	442.89
67.25	876.02	56.25	732.73	45	586.18	33.75	439.64
67	872.76	56	729.47	44.75	582.93	33.5	436.38
66.75	869.50	55.75	726.22	44.5	579.67	33.25	433.12
66.5	866.25	55.5	722.96	44.25	576.41	33	429.87
66.25	862.99	55.25	719.70	44	573.16	32.75	426.61
66	859.74	55	716.45	43.75	569.90	32.5	423.35
65.75	856.48	54.75	713.19	43.5	566.64	32.25	420.10
65.5	853.22	54.5	709.93	43.25	563.39	32	416.84
65.25	849.97	54.25	706.68	43	560.13	31.75	413.58
65	846.71	54	703.42	42.75	556.87	31.5	410.33
64.75	843.45	53.75	700.16	42.5	553.62	31.25	407.07
64.5	840.20	53.5	696.91	42.25	550.36	31	403.82
64.25	836.94	53.25	693.65	42	547.10	30.75	400.56
64	833.68	53	690.39	41.75	543.85	30.5	397.30
63.75	830.43	52.75	687.14	41.5	540.59	30.25	394.05
63.5	827.17	52.5	683.88	41.25	537.33	30	390.79
63.25	823.91	52.25	680.62	41	534.08	29.75	387.53
63	820.66	52	677.37	40.75	530.82	29.5	384.28
62.75	817.40	51.75	674.11	40.5	527.56	29.25	381.02
62.5	814.14	51.5	670.85	40.25	524.31	29	377.76
62.25	810.89	51.25	667.60	40	521.05	28.75	374.51
62	807.63	51	664.34	39.75	517.80	28.5	371.25
61.75	804.37	50.75	661.08	39.5	514.54	28.25	367.99
61.5	801.12	50.5	657.83	39.25	511.28	28	364.74
61.25	797.86	50.25	654.57	39	508.03	27.75	361.48
61	794.60	50	651.31	38.75	504.77	27.5	358.22
60.75	791.35	49.75	648.06	38.5	501.51	27.25	354.97
60.5	788.09	49.5	644.80	38.25	498.26	27	351.71
60.25	784.83	49.25	641.54	38	495.00	26.75	348.45
60	781.58	49	638.29	37.75	491.74	26.5	345.20
59.75	778.32	48.75	635.03	37.5	488.49	26.25	341.94
		48.5	631.78	37.25	485.23	26	338.68

AP-500/850 Gal. Pump Tank Calibration Chart

25.75	335.43	14.5	188.88	3.25	42.34
25.5	332.17	14.25	185.62	3	39.08
25.25	328.91	14	182.37	2.75	35.82
25	325.66	13.75	179.11	2.5	32.57
24.75	322.40	13.5	175.85	2.25	29.31
24.5	319.14	13.25	172.60	2	26.05
24.25	315.89	13	169.34	1.75	22.80
24	312.63	12.75	166.09	1.5	19.54
23.75	309.37	12.5	162.83	1.25	16.28
23.5	306.12	12.25	159.57	1	13.03
23.25	302.86	12	156.32	0.75	9.77
23	299.60	11.75	153.06	0.5	6.51
22.75	296.35	11.5	149.80	0.25	3.26
22.5	293.09	11.25	146.55	0	0.00
22.25	289.83	11	143.29		
22	286.58	10.75	140.03		
21.75	283.32	10.5	136.78		
21.5	280.07	10.25	133.52		
21.25	276.81	10	130.26		
21	273.55	9.75	127.01		
20.75	270.30	9.5	123.75		
20.5	267.04	9.25	120.49		
20.25	263.78	9	117.24		
20	260.53	8.75	113.98		
19.75	257.27	8.5	110.72		
19.5	254.01	8.25	107.47		
19.25	250.76	8	104.21		
19	247.50	7.75	100.95		
18.75	244.24	7.5	97.70		
18.5	240.99	7.25	94.44		
18.25	237.73	7	91.18		
18	234.47	6.75	87.93		
17.75	231.22	6.5	84.67		
17.5	227.96	6.25	81.41		
17.25	224.70	6	78.16		
17	221.45	5.75	74.90		
16.75	218.19	5.5	71.64		
16.5	214.93	5.25	68.39		
16.25	211.68	5	65.13		
16	208.42	4.75	61.87		
15.75	205.16	4.5	58.62		
15.5	201.91	4.25	55.36		
15.25	198.65	4	52.11		
15	195.39	3.75	48.85		
14.75	192.14	3.5	45.59		