

CP-2000 and SP-2000 Calibration Chart

Height (in.)	Volume (Gal)							
		65	1,908.92		53.75	1,578.53	42.5	1,248.14
		64.75	1,901.58		53.5	1,571.19	42.25	1,240.80
76	2,231.97	64.5	1,894.23		53.25	1,563.84	42	1,233.45
75.75	2,224.62	64.25	1,886.89		53	1,556.50	41.75	1,226.11
75.5	2,217.28	64	1,879.55		52.75	1,549.16	41.5	1,218.77
75.25	2,209.94	63.75	1,872.21		52.5	1,541.82	41.25	1,211.43
75	2,202.60	63.5	1,864.87		52.25	1,534.48	41	1,204.09
74.75	2,195.26	63.25	1,857.52		52	1,527.13	40.75	1,196.74
74.5	2,187.91	63	1,850.18		51.75	1,519.79	40.5	1,189.40
74.25	2,180.57	62.75	1,842.84		51.5	1,512.45	40.25	1,182.06
74	2,173.23	62.5	1,835.50		51.25	1,505.11	40	1,174.72
73.75	2,165.89	62.25	1,828.16		51	1,497.77	39.75	1,167.38
73.5	2,158.55	62	1,820.81		50.75	1,490.42	39.5	1,160.03
73.25	2,151.20	61.75	1,813.47		50.5	1,483.08	39.25	1,152.69
73	2,143.86	61.5	1,806.13		50.25	1,475.74	39	1,145.35
72.75	2,136.52	61.25	1,798.79		50	1,468.40	38.75	1,138.01
72.5	2,129.18	61	1,791.45		49.75	1,461.06	38.5	1,130.67
72.25	2,121.84	60.75	1,784.10		49.5	1,453.71	38.25	1,123.32
72	2,114.49	60.5	1,776.76		49.25	1,446.37	38	1,115.98
71.75	2,107.15	60.25	1,769.42		49	1,439.03	37.75	1,108.64
71.5	2,099.81	60	1,762.08		48.75	1,431.69	37.5	1,101.30
71.25	2,092.47	59.75	1,754.74		48.5	1,424.35	37.25	1,093.96
71	2,085.13	59.5	1,747.39		48.25	1,417.00	37	1,086.61
70.75	2,077.78	59.25	1,740.05		48	1,409.66	36.75	1,079.27
70.5	2,070.44	59	1,732.71		47.75	1,402.32	36.5	1,071.93
70.25	2,063.10	58.75	1,725.37		47.5	1,394.98	36.25	1,064.59
70	2,055.76	58.5	1,718.03		47.25	1,387.64	36	1,057.25
69.75	2,048.42	58.25	1,710.68		47	1,380.29	35.75	1,049.90
69.5	2,041.07	58	1,703.34		46.75	1,372.95	35.5	1,042.56
69.25	2,033.73	57.75	1,696.00		46.5	1,365.61	35.25	1,035.22
69	2,026.39	57.5	1,688.66		46.25	1,358.27	35	1,027.88
68.75	2,019.05	57.25	1,681.32		46	1,350.93	34.75	1,020.54
68.5	2,011.71	57	1,673.97		45.75	1,343.58	34.5	1,013.19
68.25	2,004.36	56.75	1,666.63		45.5	1,336.24	34.25	1,005.85
68	1,997.02	56.5	1,659.29		45.25	1,328.90	34	998.51
67.75	1,989.68	56.25	1,651.95		45	1,321.56	33.75	991.17
67.5	1,982.34	56	1,644.61		44.75	1,314.22	33.5	983.83
67.25	1,975.00	55.75	1,637.26		44.5	1,306.87	33.25	976.48
67	1,967.65	55.5	1,629.92		44.25	1,299.53	33	969.14
66.75	1,960.31	55.25	1,622.58		44	1,292.19	32.75	961.80
66.5	1,952.97	55	1,615.24		43.75	1,284.85	32.5	954.46
66.25	1,945.63	54.75	1,607.90		43.5	1,277.51	32.25	947.12
66	1,938.29	54.5	1,600.55		43.25	1,270.16	32	939.77
65.75	1,930.94	54.25	1,593.21		43	1,262.82	31.75	932.43
65.5	1,923.60	54	1,585.87		42.75	1,255.48	31.5	925.09
65.25	1,916.26							

CP-2000 and SP-2000 Calibration Chart

31.25	917.75	20	587.36	8.75	256.97
31	910.41	19.75	580.02	8.5	249.63
30.75	903.06	19.5	572.68	8.25	242.29
30.5	895.72	19.25	565.33	8	234.94
30.25	888.38	19	557.99	7.75	227.60
30	881.04	18.75	550.65	7.5	220.26
29.75	873.70	18.5	543.31	7.25	212.92
29.5	866.35	18.25	535.97	7	205.58
29.25	859.01	18	528.62	6.75	198.23
29	851.67	17.75	521.28	6.5	190.89
28.75	844.33	17.5	513.94	6.25	183.55
28.5	836.99	17.25	506.60	6	176.21
28.25	829.65	17	499.26	5.75	168.87
28	822.30	16.75	491.91	5.5	161.52
27.75	814.96	16.5	484.57	5.25	154.18
27.5	807.62	16.25	477.23	5	146.84
27.25	800.28	16	469.89	4.75	139.50
27	792.94	15.75	462.55	4.5	132.16
26.75	785.59	15.5	455.20	4.25	124.81
26.5	778.25	15.25	447.86	4	117.47
26.25	770.91	15	440.52	3.75	110.13
26	763.57	14.75	433.18	3.5	102.79
25.75	756.23	14.5	425.84	3.25	95.45
25.5	748.88	14.25	418.49	3	88.10
25.25	741.54	14	411.15	2.75	80.76
25	734.20	13.75	403.81	2.5	73.42
24.75	726.86	13.5	396.47	2.25	66.08
24.5	719.52	13.25	389.13	2	58.74
24.25	712.17	13	381.78	1.75	51.39
24	704.83	12.75	374.44	1.5	44.05
23.75	697.49	12.5	367.10	1.25	36.71
23.5	690.15	12.25	359.76	1	29.37
23.25	682.81	12	352.42	0.75	22.03
23	675.46	11.75	345.07	0.5	14.68
22.75	668.12	11.5	337.73	0.25	7.34
22.5	660.78	11.25	330.39	0	0.00
22.25	653.44	11	323.05		
22	646.10	10.75	315.71		
21.75	638.75	10.5	308.36		
21.5	631.41	10.25	301.02		
21.25	624.07	10	293.68		
21	616.73	9.75	286.34		
20.75	609.39	9.5	279.00		
20.5	602.04	9.25	271.65		
20.25	594.70	9	264.31		